

MINISTERE DE L'EQUIPEMENT, DES TRANSPORTS, DU LOGEMENT, DU TOURISME ET DE LA MER



Bureau de Vérifications Techniques
31, Rue de Montjean
94 266 FRESNES CEDEX
FRANCE

TEL : 01 46 68 50 30
FAX : 01 46 68 53 35

S.A.S. au capital de 82 650 Euros RCS CRETEIL B 309 306 918 APE 7701/743B

TRANSPORT DES MARCHANDISES DANGEREUSES CERTIFICAT D'AGREMENT DE TYPE D'EMBALLAGE

Applicant : TIAG-INDUSTRIES
16 / 18 avenue M. Saulnier
78140 VELIZY VILLACOUBLAY FRANCE

N° 0011

Site of production : Indice 2
F-19800 SAINT PRIEST DE GIMEL

REFERENCE DOCUMENTS :

- Road transport : ADR, to date in 01/01/2003
- Rail transport : RID, to date in 01/01/2003
- Transport by waterway : ADNR, to date in 01/01/2003
- Maritime transport : IMDG code to date in 01/01/2003
- Air transport : Doc OACI 9284 AN905, to date in 2003/2004

DESCRIPTION OF THE TYPE OF PACKAGING : Sample record n° 0259

- Manufacturer : TIAG INDUSTRIES / F-19800 SAINT PRIEST DE GIMEL
- Packaging code : 1H1
- Type, materials : Fût, Plastique
- Construction method : Extrusion-soufflage
- Commercial reference : Fût 120 L, OP, 4,5 kg
- Constituent raw material : PEHD Finathène 56020 S (Atofina)
 - Density : 0,952
 - Melt index 190°C 21,6 Kg : 2g / 10 min
- Drawings : FT/29 Ind A - RTS504869c, RTS504954a
- Nominal capacity : 120 L
- Brimful capacity : 126 L
- Empty weight (tare) : 4,53 = (4,5 + 0,03) Kg
- Overall external dimensions : Ø 0,495 x 0,8 m
- Minimum thickness : 2,2 mm
- Closure : Bonde 2" + joint Pe - fab. : Greif Fermetures - réf. : BCS 56 x 4 6N
(Identification Plastiplug/Tri Sure R15/A1)
Bonde 3/4 " + joint Pe - fab. : Greif Fermetures - réf. : 3/4" FL
(Identification Plastiplug/Tri Sure R21/R13)
- Handling : Poignée moulée sur la partie supérieure
- Decompression : Néant
- Particularities : Sans


AUTHORIZED AREAS OF USE : Dangerous liquids in the following conditions :

- Packaging group : II,III
- Max. Density : 1,8
- Maximum authorized vapour pressure at +50°C : 171 kPa
- Stacking : height : 3 m

TESTS AND MARKING :

Satisfactory test results, according to report : BVT 25546 indice 0 du 28/01/1994

Marking model to be placed on the condition that the regulatory measures are respected

 1H1 / Y 1,8 / 200 / --*
F / BVT 25546 / TIAG INDUSTRIES

* See the appendix to the approval certificate

The French text serves as a basis for the translation, and should any difference exist between the French text and a text in another language, the French text will prevail.

Issued in Fresnes,

On 30/09/2004

For a period of five years

Manager of the approved test laboratory
Mrs E. FRAGU

